

DRY SANDS

- Silikaat's sieved dry sand is made from Männiku quarry's sand by drying and sieving. Dry sand is packed in bags from 25 kg to 1000 kg.
- For de-icing sidewalks and parking lots aggregate fraction 2,0-6,0 mm; in 7,5 kg plastic bucket.
- Sandblasting sand and other fractions can also be bought without a package (in bulk).

| Recommended use/ Fraction | Home and garden | Construction and construction mixtures | Sandblasting works | Specifics | Availability |
|---------------------------|--|--|---|---|---------------------|
| 0 - 0,6 mm | snail protection | fine putty, mixtures on potter works and plastering works | stainless steel, aluminum, finishing of tombstones, wood cleaning, final finishing before painting, glass | mold sand for metal casting | 1 t |
| 0 - 0,8 mm | airing grass - filling the joints of pavement stones | mortars and plasters - joint filler for pavement stones | softer structured metal products - car wheel rims with light rust | for making kinetic sand | in bulk, 25 kg, 1 t |
| 0 - 1,25 mm | | cement putty, plaster mixtures, mortars, concrete | | brake slots for golf fields | 1 t |
| 0,5 - 1,25 mm | artificial grass, maintenance of lawns | cement putty, plaster mixtures, mortars, concrete | cleaning of stone and plaster facades | filter sand, fluidized bed boilers in a co-generation plant | 1 t |
| 0 - 2 mm | covering pathways or designing borders - children's sand boxes | mortars and plasters | cleaning granite tiles and other such details | beach volleyball courts - hipodromes - graveyards | in bulk, 25 kg, 1 t |
| 0,63 - 2 mm | houseplant pots, cat litter boxes, aquariums | potter works, concrete aggregate, leveling under pavement | primary processing of tin rims and metal products with rust and a thick layer of paint | filter sand | 25 kg, 1 t |
| 1 - 2 mm | | concrete aggregate - filtering layers - covering tarred road sections - load-bearing layer for floating floors | cleaning the water line of ships, speedboats and other such vehicles when docking | filter sand - filter system for trams and locomotives - covering tarred road sections in the summer | 1 t |
| 2 - 6 mm | de-icing - coating decorative squares - landscaping | coarse aggregate for concrete - creating filtering surface layers | removing particularly thick layers, can be used in stead of cleaning with pellets | filter sand - de-icing - gardening and landscaping | in bulk 25 kg, 1 t |
| 2 - 20 mm | coating pathways and squares | building drainage systems | | aggregate for wetlands and clay soil - gardening and landscaping | in bulk |